

# MATERIAL SAFETY DATA SHEET



Page: 1  
DATE PREPARED: 03/15/2004  
MSDS No: 400240a  
**UVR-120Y**

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: UVR-120Y  
Product Description: UVR Legend Ink  
Product Name: UVR-120Y  
Chemical Family: UV Curable Legend Ink

### MANUFACTURER:

Taiyo America, Inc.  
2675 Antler Drive  
Carson City, NV 89701  
Customer Service: 775-885-9959

### 24 HR. EMERGENCY TELEPHONE

NUMBERS:  
Emergency Contact: Phillip Harrison  
Emergency Phone: 775-885-9959

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

	wt.%	CAS Registry #
Trimethylolpropane Triacrylate	10 – 12	15625-89-5
2-Hydroxyethyl Methacrylate	8 – 10	868-77-9
Epoxy Acrylate Resin	(Trade Secret)	8 – 10
Acrylate Resin	(Trade Secret)	6 – 9

### COMMENTS:

Trimethylolpropane Triacrylate  
Primary Irritation Index (PII): 4.8 - 2.2

## 3. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

#### PHYSICAL APPEARANCE:

Viscous yellow ink. Slight Mild Odor.

### POTENTIAL HEALTH EFFECTS

#### EYES:

May cause irritation of the eyes.

#### SKIN:

May cause skin irritation.

May cause skin sensitization, an allergic reaction, which becomes evident on re-exposure to this material.

#### INGESTION:

Swallowing large amounts of this material may be harmful.

**INHALATION:**

May cause respiratory tract irritation.  
High vapor concentrations may cause headaches, dizziness and nausea.

**SUBCHRONIC/CHRONIC TOXICITY****CHRONIC:**

Prolonged or repeated contact can result in drying of the skin which may result in skin irritation and dermatitis (rash).

**CARCINOGENICITY:**

NTP, IARC, and OSHA sources checked: Not Listed.

---

**4. FIRST AID MEASURES****EYES:**

Immediately flush eyes with plenty of water for 15 minutes. Get medical attention, if irritation persists.

**SKIN:**

Wash skin with soap and plenty of water.

**INGESTION:**

Do not induce vomiting. Give milk or water. Get medical attention.

**INHALATION:**

If breathing becomes difficult, remove to fresh air.  
If symptoms persist give oxygen and seek medical attention.

---

**5. FIRE FIGHTING MEASURES**

Flashpoint and Method: 230°F 110°C SETA Flash CC

**FLAMMABLE CLASS:**

OSHA: Combustible  
DOT: Not Classified

**GENERAL HAZARD:**

The Uniform Fire Code flammability rating for this product is: Class III-B Combustible Liquid.  
If burning, this material may produce hazardous fumes or hazardous decomposition products.

**EXTINGUISHING MEDIA:**

Use carbon dioxide, foam, dry chemical or water spray when fighting fires involving this material.

---



**HAZARDOUS COMBUSTION PRODUCTS:**

Combustion products may be toxic. May produce various carbon oxides and hydrocarbons.

**EXPLOSION HAZARDS:**

Sealed containers may build up pressure and rupture when exposed to high heat (fire).

**FIRE FIGHTING PROCEDURES:**

Remove sealed containers from the vicinity of the fire.

Use normal fire fighting procedures for burning liquids.

**FIRE FIGHTING EQUIPMENT:**

Use self-contained breathing apparatus with full facepiece operated in the positive pressure demand mode with appropriate turn-out gear.

---

**6. ACCIDENTAL RELEASE MEASURES**

**SMALL SPILL:**

Absorb the spilled material with inert material. Scrub the area with detergent and water.

**ENVIRONMENTAL PRECAUTIONS:**

**WATER SPILL:**

Contain, minimize dispersion and collect as soon as possible.

**LAND SPILL:**

Prevent from entering drain, sewer, stream or other bodies of water. Transfer absorbent, soil and other materials to containers for disposal.

**SPECIAL PROTECTIVE EQUIPMENT:**

Protective eyewear, impervious gloves, air purifying respirator recommended.

---

**7. HANDLING AND STORAGE**

**HANDLING:**

Avoid contact with skin, eyes and clothing. Use only with adequate ventilation.

**STORAGE:**

Store in a cool place in original sealed container away from sunlight and heat.

Recommended storage below 68 F to maintain shelf life.

---

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**ENGINEERING CONTROLS:**

Good general mechanical ventilation recommended.

---



---

#### **PERSONAL PROTECTION**

##### **EYES AND FACE:**

Wear safety glasses with side shields, goggles or face shield to prevent splashes into the eyes.

##### **SKIN:**

In general avoid skin contact, wear impervious gloves.

##### **RESPIRATORY:**

Not necessary for adequately ventilated work area.

##### **PROTECTIVE CLOTHING:**

As necessary to avoid contact with skin.

##### **WORK HYGIENIC PRACTICES:**

Wash hands with soap and water after using material. Do not use solvent to remove product from skin.

##### **OTHER USE PRECAUTIONS:**

This product contains inorganic fillers. In normal use as a liquid soldermask the inorganic fillers are not hazardous. Dust from sanding, drilling or routing of the cured soldermask may pose an inhalation hazard.

---

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical State: Liquid

Odor: Slight mild organic solvent odor.

Appearance: Yellow viscous liquid.

Percent Volatile: 0

Vapor Pressure: <0.01 mmHg at 20°C

Vapor Density: ~1.1 (Air = 1)

Boiling Point: Not Established

Freezing Point: Not Established

Melting Point: None

Solubility in Water: Not Established

Evaporation Rate: <0.1 (n-Butyl Acetate=1)

Specific Gravity: 1.5 (water=1)

(VOC): 0

##### **COMMENTS:**

Contains no components volatile at normal storage and use temperatures.

---

## **10. STABILITY AND REACTIVITY**

STABLE: Yes

---



**HAZARDOUS POLYMERIZATION:** No

**STABILITY:**

This product is stable under normal operating conditions. High temperatures may cause curing or partial curing of the material.

**POLYMERIZATION:**

Polymerization may occur at elevated temperatures and from UV exposure. Polymerization is not considered hazardous.

**CONDITIONS TO AVOID:**

Avoid high temperatures, sunlight.

**HAZARDOUS DECOMPOSITION:**

Normal combustion products.

**INCOMPATIBLE MATERIALS:**

Oxidizers, peroxides, strong acids and bases, amines and active epoxy curing agents.

---

## **11. TOXICOLOGICAL INFORMATION**

**GENERAL COMMENTS:**

No specific toxicological data is available for this product.

---

## **12. ECOLOGICAL INFORMATION**

**GENERAL COMMENTS:**

No specific environmental data is available.

---

## **13. DISPOSAL CONSIDERATIONS**

**PRODUCT DISPOSAL:**

Dispose of in accordance with all Federal, State and Local regulations. Keep out of sewers and waterways.

**RCRA/USPA WASTE INFORMATION:**

Not a RCRA waste material.

---



---

## 14. TRANSPORT INFORMATION

**SPECIAL SHIPPING NOTES:**  
Not DOT regulated.

---

## 15. REGULATORY INFORMATION

### UNITED STATES

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**  
TSCA Regulatory: This product complies with all applicable rules or orders under TSCA.

**RCRA STATUS:**  
Not a RCRA hazardous waste.

### CANADA

**CANADIAN ENVIRONMENTAL PROTECTION ACT:**  
This product contains substances not included in the DSL or the NDSL, in the following concentrations in % by weight:  
Polymer: 9.2

---

## 16. OTHER INFORMATION

Approved by: Phillip Harrison Title: Plant Manager  
Approval date: 07/15/2004  
Information Contact: Phillip Harrison

**REVISION SUMMARY**  
Revision #: 3

This MSDS replaces the September 17, 2003 MSDS. Any changes in information are as follows:  
In Section 1  
Msds number Date Prepared

In Section 9  
Specific Gravity (from) Specific Gravity (to) VOC (from) Section 9 Footnotes

In Section 15  
CEPA

In Section 16  
Manufacturer Disclaimer

---



Page: 7

DATE PREPARED: 03/15/2004

MSDS No: 400240a

**UVR-120Y**

---

**HMIS CODES**

Fire: 1    Health: 2    Reactivity: 2

**MANUFACTURER SUPPLEMENTAL NOTES:**

This product contains no environmentally restricted substances as listed in Sony Technical Standard SS-00259 second edition.

**MANUFACTURER DISCLAIMER:**

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

---